

Injector Performance Table

Water Suction Capacity (METRIC)

REV 2014

Operating Pressure kg/cm ²		Model 283 15mm Threads		Model 287 15mm Threads		Model 384 15mm Threads		Model 384X 15mm Threads		Model 484 15mm & 20mm Threads		Model 484X 20mm Threads	
Injector Inlet	Injector Outlet	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min
0.35	0.00	0.64	0.20	1.1	0.33	2.7	0.65	2.7	0.73	4.5	0.92	4.5	1.4
	0.07		0.13		0.16		0.54		0.54		0.65		1.0
	0.14		0.06		0.11		0.47		0.25		0.42		0.75
	0.21				<0.10		0.32						0.46
	0.28		(0.25)		(0.25)		(0.27)		(0.20)		(0.31)		(0.25)
0.70	0.00	0.91	0.30	1.2	0.39	3.8	0.96	3.8	1.1	6.4	1.1	6.4	1.8
	0.14		0.18		0.30		0.72		0.85		0.88		1.4
	0.35		0.07		0.12		0.48		0.12		0.38		0.74
	0.49				<0.10		0.13				0.17		0.23
	0.56		(0.49)		(0.54)		(0.58)		(0.46)		(0.59)		(0.53)
1.05	0.00	1.1	0.34	1.6	0.43	4.6	0.84	4.6	1.7	7.8	1.1	7.8	2.4
	0.35		0.17		0.26		0.71		0.73		0.72		1.3
	0.49		0.11		0.18		0.53		0.26		0.52		0.98
	0.70				<0.10		0.30						
	0.84		(0.74)		(0.81)		(0.91)		(0.68)		(0.88)		(0.61)
1.41	0.00	1.2	0.37	1.9	0.44	5.4	0.82	5.4	1.8	9.0	1.1	9.0	2.4
	0.35		0.23		0.38		0.83		1.0		0.98		1.7
	0.70		0.13		0.21		0.58		0.19		0.59		0.84
	0.84		0.03		0.12		0.40				0.49		0.53
	1.05		(1.05)		<0.10		(1.16)		(0.87)		(1.20)		(0.93)
1.76	0.00	1.3	0.37	2.2	0.49	6.0	0.89	6.0	2.0	10.1	1.1	10.1	2.4
	0.35		0.20		0.44		0.89		1.4		1.0		2.0
	0.70		0.16		0.28		0.80		0.70		0.86		1.3
	1.05		0.04		0.15		0.42				0.46		0.62
	1.41		(1.30)		(1.37)		(1.44)		(1.06)		(1.52)		(1.16)
2.11	0.00	1.5	0.38	2.5	0.50	6.6	0.89	6.6	2.1	11.1	1.0	11.1	2.5
	0.35		0.37		0.50		0.91		1.5		1.0		2.4
	0.70		0.24		0.35		0.87		1.0		1.0		1.8
	1.05		0.15		0.23		0.67		0.44		0.71		1.0
	1.41		0.05		0.11		0.28				0.44		(1.20)
2.46	0.00	1.5	0.38	2.6	0.51	7.1	0.91	7.1	2.1	11.9	1.0	11.9	2.5
	0.35		0.38		0.50		0.91		1.8		1.0		2.4
	0.70		0.30		0.43		0.91		1.2		1.0		2.1
	1.05		0.21		0.32		0.86		0.67		1.0		1.5
	1.41		0.11		0.19		0.59				0.70		0.93
2.81	0.00	1.6	0.38	2.8	0.51	7.6	0.89	7.6	2.1	12.8	1.0	12.8	2.5
	0.35		0.38		0.51		0.89		1.9		1.1		2.4
	0.70		0.35		0.47		0.88		1.5		1.1		2.4
	1.05		0.26		0.40		0.88		0.89		1.1		1.8
	1.41		0.16		0.27		0.79		0.22		0.96		1.3
3.16	0.00	1.7	0.38	3.1	0.51	8.0	0.86	8.0	2.1	13.5	1.0	13.5	2.6
	0.35		0.37		0.51		0.87		1.9		1.0		2.4
	0.70		0.31		0.44		0.86		1.9		1.1		2.3
	1.05		0.21		0.35		0.87		0.69		1.0		2.2
	1.41		0.17		0.25		0.76		<0.10		0.87		1.1
3.52	0.00	1.8	0.38	3.2	0.52	8.5	0.89	8.5	2.1	14.3	1.0	14.3	2.6
	0.35		0.38		0.52		0.89		2.0		1.0		2.5
	0.70		0.38		0.52		0.89		2.0		1.1		2.4
	1.05		0.36		0.50		0.89		1.5		1.1		2.3
	1.41		0.30		0.37		0.85		0.96		1.1		1.8
2.11	0.00	1.8	0.22	2.74	0.28	8.5	0.85	8.5	1.0	14.3	1.0	14.3	2.6
	0.35		0.13		0.19		0.63		0.42		0.80		1.8
	0.70		0.04		<0.10		0.38				0.49		0.51
	1.05		(2.60)		(2.74)		(2.78)		(2.02)		(2.88)		(2.04)

*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright® 2015

Mazzei Injector Company, LLC
500 Rooster Drive, Bakersfield, CA 93307-9555 USA
www.mazzei.net

Injector Performance Table

Water Suction Capacity (METRIC)

REV 2014

Operating Pressure		Model 283		Model 287		Model 384		Model 384X		Model 484		Model 484X	
kg/cm ²		15mm Threads		15mm Threads		15mm Threads		15mm Threads		15mm & 20mm Threads		20mm Threads	
Injector Inlet	Injector Outlet	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min						
4.22	0.00	2.0	0.38	3.5	0.52	9.3	0.86	9.3	2.1	15.6	1.1	15.6	2.6
	0.35		0.38		0.52		0.86		2.1		1.1		2.6
	0.70		0.38		0.49		0.85		2.1		1.1		2.4
	1.05		0.38		0.49		0.85		2.0		1.1		2.4
	1.41		0.36		0.49		0.84		1.5		1.1		2.3
	2.11		0.24		0.36		0.78		.57		1.0		1.4
	2.46		0.15		0.26		0.73		<0.10		0.96		
	2.81		0.08		0.17		0.52				0.75		
	3.16		*(3.20)		<0.10		*(3.33)		0.15		*(3.57)		*(2.43)
	0.00		0.38		0.52		0.76		2.2		1.1		2.6
4.92	0.35	2.2	0.38	3.8	0.52	10.0	0.76	10.0	1.9	16.9	1.0	16.9	2.2
	0.70		0.38		0.52		0.76		2.2		1.1		2.6
	1.05		0.38		0.52		0.77		2.1		1.0		2.4
	1.41		0.38		0.52		0.76		2.0		1.0		2.3
	2.11		0.33		0.47		0.77		1.9		1.0		1.9
	2.81		0.18		0.30		0.75		1.1		1.0		1.0
	3.16		0.12		0.22		0.69		0.21		0.84		
	3.52		0.05		0.11		0.47				0.71		
	3.87		*(3.80)		*(3.87)		*(3.68)		*(2.92)		*(4.11)		*(2.86)
	0.00		0.38		0.52		0.73		2.1		1.0		2.6
5.62	0.35	2.3	0.38	4.0	0.52	10.7	0.73	10.7	1.9	18.0	1.0	18.0	2.5
	0.70		0.38		0.52		0.73		2.1		1.0		2.6
	1.05		0.38		0.52		0.73		2.1		1.0		2.6
	1.41		0.38		0.52		0.73		2.0		1.0		2.5
	2.11		0.38		0.51		0.73		1.6		1.0		2.5
	2.81		0.28		0.40		0.73		0.74		0.99		1.7
	3.52		0.15		0.26		0.71				0.94		0.43
	4.22				<0.10		0.43		*(3.32)		*(4.64)		*(3.65)
	4.57		*(4.26)		*(4.43)		*(4.35)						
	0.00		0.38		0.52		0.70		2.2		0.86		2.6
6.33	0.35	2.5	0.38	4.3	0.52	11.4	0.70	11.4	1.8	19.1	0.86	19.1	2.4
	0.70		0.38		0.52		0.70		1.1		0.86		2.1
	1.41		0.38		0.52		0.70		0.30		0.86		1.6
	2.11		0.38		0.52		0.69				0.84		
	2.81		0.36		0.50		0.69				0.26		
	3.52		0.22		0.36		0.69						
	4.22		0.10		0.22		0.69						
	4.92				<0.10		0.29		*(3.73)		*(5.20)		*(3.81)
	5.27		*(4.78)		*(4.99)		*(4.99)						
	0.00		0.38		0.52		0.70		2.2		0.86		2.6
7.03	0.35	2.6	0.38	4.5	0.49	12.0	0.68	12.0	1.9	20.2	0.83	20.2	2.5
	0.70		0.38		0.49		0.68		1.8		0.83		2.5
	1.41		0.38		0.49		0.69		0.77		0.83		2.2
	2.11		0.38		0.49		0.68				0.83		1.7
	2.81		0.38		0.47		0.69				0.83		
	3.52		0.32		0.45		0.69				0.83		
	4.22		0.19		0.33		0.69				0.81		
	4.92		0.07		0.19		0.66						
	5.62				*(5.54)		*(5.55)		*(4.15)		*(5.83)		*(4.19)
	0.00		0.38		0.40		0.68		2.1		0.77		2.8
8.44	0.35	2.9	0.38	5.0	0.40	13.1	0.68	13.1	1.9	22.1	0.77	22.1	2.3
	0.70		0.38		0.40		0.68		1.5		0.77		2.0
	1.41		0.38		0.40		0.68		0.88		0.77		1.5
	2.11		0.38		0.40		0.68		0.13		0.76		1.2
	2.81		0.38		0.38		0.68				0.73		
	3.52		0.35		0.38		0.68						
	4.22		0.33		0.37		0.68						
	4.92		0.25		0.30		0.68						
	5.62		0.15		0.23		0.68						
	6.33		0.06		<0.10		0.54		*(5.01)		*(7.01)		*(5.00)
	7.03				*(6.54)		*(6.68)						

*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright® 2015

Mazzei Injector Company, LLC
500 Rooster Drive, Bakersfield, CA 93307-9555 USA
www.mazzei.net

Injector Performance Table

Water Suction Capacity (METRIC)

REV 2014

Operating Pressure kg/cm ²		Model 584 15mm & 20mm Threads		Model 684 20mm Threads		Model 878-03 25mm Threads		Model 885X-03 25mm Threads		Model 1078-03 25mm Threads		Model 1583 40mm Threads	
Injector Inlet	Injector Outlet	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min
0.35	0.00		1.8		1.7		3.9		4.9		6.4		8.5
	0.07		1.8		1.2		2.2		3.9		2.9		5.3
	0.14		1.7		0.87		1.5		2.6		1.3		3.3
	0.21		1.6		0.41		0.46		0.97		0.17		
	0.28	*(0.31)	0.63	(0.30)	0.35	(0.28)		(0.28)		(0.28)		(0.31)	
	0.00		1.7		1.7		5.9		7.3		6.6		13.8
0.70	0.14		1.7		1.7		19.5		19.1		29.3		57.4
	0.35		1.7		1.1		2.3		5.7		2.6		4.9
	0.49		0.83		0.68		0.99		2.8		1.2		2.6
	0.56	(0.63)	0.69	(0.60)	0.38	(0.61)	0.23	(0.53)	(0.57)		0.27		(0.61)
	0.00		1.7		1.6		5.5		8.5		6.3		14.2
	0.35		1.7		1.6		3.9		5.2		5.0		10.3
1.05	0.49		1.7		1.5		2.8		3.6		4.0		7.8
	0.70		0.88		0.81		1.4		1.2		2.1		5.4
	0.84	(0.95)	0.69	(0.91)	0.44	(0.88)	0.45	(0.77)	(0.92)		1.0		(0.91)
	0.00		1.5		1.5		5.2		8.9		6.1		14.3
	0.35		1.5		1.5		5.0		7.4		6.0		12.9
	0.70		1.4		1.5		3.0		3.6		4.4		9.0
1.41	0.84		1.2		1.1		2.1		2.2		3.2		8.3
	1.05		0.92	(1.16)	0.65	(1.16)	1.3	(0.98)	(1.22)		1.9		4.1
	0.00		1.5		1.5		5.1		9.0		6.0		14.3
	0.35		1.5		1.5		5.1		8.5		6.0		12.9
	0.70		1.4		1.5		4.6		6.0		5.6		9.0
	1.05		1.2		1.1		2.8		2.4		4.3		9.3
1.76	1.41		0.92	(1.16)	0.32	(1.48)	1.2	(1.20)	(1.54)		2.0		(1.55)
	1.41		1.5		1.5		5.1		9.0		6.0		14.3
	1.76		1.5		1.5		5.1		8.5		6.0		14.2
	1.76		1.5		1.5		4.6		46.3		5.6		90.8
	1.76		1.3		1.5		2.8		(1.20)		4.3		12.2
	1.76		0.76	(1.48)	0.32		1.2		(1.54)		2.0		3.0
2.11	0.00		1.5		1.5		5.0		9.0		5.9		14.2
	0.35		1.6		1.5		4.9		8.8		5.9		14.2
	0.70		1.5		1.5		4.8		7.9		5.9		99.4
	1.05		1.5		1.5		4.1		4.3		5.1		13.3
	1.41		1.1		0.92		2.2		0.90		3.4		7.9
	1.76		0.72	(1.83)	0.42	(1.84)	0.57	(1.44)	(1.83)		1.1		(1.83)
2.46	0.00		1.6		1.5		5.0		8.9		5.9		14.3
	0.35		1.6		1.5		5.0		8.9		5.9		14.2
	0.70		1.6		1.5		4.8		8.5		5.9		107
	1.05		1.5		1.5		4.7		6.7		5.7		14.1
	1.41		1.3		1.5		3.3		3.4		4.6		10.4
	1.76		1.0	(2.07)	0.81	(2.12)	1.9	(1.69)	(2.11)		2.9		(2.07)
2.81	0.00		1.6		1.5		4.8		8.8		5.8		14.3
	0.35		1.6		1.5		4.8		8.9		5.8		14.4
	0.70		1.6		1.5		4.8		8.7		5.8		14.3
	1.05		1.6		1.5		4.8		58.6		5.8		115
	1.41		1.5		1.5		4.6		5.7		5.7		12.1
	1.76		1.3		1.5		3.1		2.3		4.5		9.6
3.16	2.11		0.94	(2.46)	0.68	(2.42)	1.7	(1.90)	(2.42)		2.6		(2.35)
	0.00		1.6		1.5		5.0		8.8		5.8		14.3
	0.35		1.6		1.5		5.0		8.8		5.8		14.4
	0.70		1.6		1.5		5.0		8.7		5.8		14.3
	1.05		1.6		1.5		4.9		8.5		5.8		14.1
	1.41		1.6		1.5		4.9		7.0		5.9		13.4
3.52	1.76		1.4		1.5		4.2		4.6		5.4		11.0
	2.11		1.2		1.3		2.7		1.4		4.1		7.1
	2.46		0.85	(2.64)	0.53	(2.70)	1.3	(2.18)	(2.72)		2.3		(2.64)
	0.00		1.6		1.5		4.7		8.8		5.8		14.3
	0.35		1.6		1.5		4.7		8.8		5.8		14.3
	0.70		1.6		1.5		4.7		8.8		5.8		14.2
3.52	1.05		1.6		1.5		4.7		8.7		5.8		14.2
	1.41		1.6		1.5		4.7		8.0		5.8		14.1
	1.76		1.5		1.5		4.3		6.7		5.8		12.8
	2.11		1.3		1.0		3.5		3.7		5.4		10.8
	2.46		0.99	(2.95)	0.57	(2.97)	2.3	(2.53)	(3.09)		4.0		7.6
	2.81		(3.16)	0.17	0.42	(2.97)	0.60	(2.53)	(2.09)		2.2		(2.95)

*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright® 2015

Mazzei Injector Company, LLC
500 Rooster Drive, Bakersfield, CA 93307-9555 USA

www.mazzei.net

Injector Performance Table

REV 2014

Water Suction Capacity (METRIC)													
Operating Pressure		Model 584		Model 684		Model 878-03		Model 885X-03		Model 1078-03		Model 1583	
kg/cm ²		15mm & 20mm Threads		20mm Threads		25mm Threads		25mm Threads		25mm Threads		40mm Threads	
Injector Inlet	Injector Outlet	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min
4.22	0.00	27.4	1.6	45.9	1.5	47.9	4.5	46.7	8.8	71.8	5.8	141	14.4
	0.35		1.6		1.5		4.5		8.8		5.8		14.4
	0.70		1.6		1.6		4.5		8.8		5.8		14.4
	1.05		1.6		1.5		4.5		8.8		5.8		14.3
	1.41		1.6		1.5		4.5		8.7		5.8		14.3
	2.11		1.6		1.5		4.4		6.9		5.8		13.0
	2.46		1.5		1.5		3.9		4.6		5.7		11.5
	2.81		1.2		0.85		2.6		2.0		4.8		9.3
	3.16		*(3.76)		0.90		*(3.60)		*(3.02)		*(3.59)		5.1
	0.00		1.6		1.6		4.6		8.8		5.8		14.4
4.92	0.35	29.6	1.6	49.6	1.6	51.7	4.6	50.5	8.8	77.5	5.8	152	14.4
	0.70		1.6		1.6		4.6		8.8		5.8		14.4
	1.05		1.6		1.6		4.6		8.8		5.8		14.4
	1.41		1.6		1.6		4.6		8.8		5.8		14.4
	2.11		1.6		1.6		4.6		8.5		5.8		14.2
	2.81		1.6		1.6		4.2		5.5		5.8		12.5
	3.16		1.4		1.3		2.9		2.8		5.1		10.0
	3.52		1.0		0.66		1.9				3.4		7.8
	3.87		*(4.43)		0.57		*(4.10)		0.81		*(4.14)		2.7
	0.00		1.6		1.6		4.6		8.8		5.9		14.6
5.62	0.35	31.6	1.6	53.1	1.6	55.3	4.6	53.9	8.8	82.9	5.9	162	14.6
	0.70		1.6		1.6		4.6		8.8		5.9		14.6
	1.05		1.6		1.6		4.6		8.8		5.9		14.6
	1.41		1.6		1.6		4.6		8.8		5.9		14.6
	2.11		1.6		1.6		4.6		8.8		5.9		14.6
	2.81		1.6		1.6		4.6		7.8		5.9		13.9
	3.52		1.5		1.6		3.5		3.7		5.7		11.1
	4.22		1.0		0.98		1.6				3.3		5.8
	4.57		*(5.10)		0.49		0.31		0.50		*(4.82)		0.75
	0.00		1.6		1.6		4.6		8.8		2.0		*(4.92)
6.33	0.35	33.6	1.7	56.3	1.6	58.7	4.6	57.2	8.9	87.9	5.9	172	14.4
	0.70		1.7		1.6		4.6		8.8		5.9		14.4
	1.41		1.7		1.6		4.6		8.8		5.9		14.4
	2.11		1.7		1.6		4.6		8.6		6.0		14.4
	2.81		1.7		1.6		4.4		6.5		5.9		13.7
	3.52		1.7		1.6		3.0		2.1		5.3		11.2
	4.22		1.5		1.6		1.1				2.4		3.0
	4.92		0.83		1.6		<0.10		*(4.64)		*(5.41)		*(5.14)
	5.27		*(5.66)		0.33		0.84				1.2		
	0.00		1.7		1.6		4.6		8.9		5.9		14.4
7.03	0.35	35.4	1.8	59.3	1.5	61.8	4.8	60.3	8.9	92.7	5.9	182	14.6
	0.70		1.8		1.5		4.8		8.9		5.9		14.6
	1.41		1.8		1.5		4.8		8.8		5.9		14.6
	2.11		1.8		1.5		4.8		8.8		5.9		14.6
	2.81		1.8		1.5		4.7		8.2		5.9		14.4
	3.52		1.8		1.5		4.2		5.5		5.9		13.0
	4.22		1.7		1.5		2.8		2.0		5.1		9.2
	4.92		1.4		1.5		0.82		*(5.13)		1.9		*(5.72)
	5.62		1.0		1.3				*(6.05)		1.6		
	0.00		2.0		1.5		4.7		8.8		5.9		14.6
8.44	0.35	38.7	2.0	65.0	1.5	67.7	4.7	66.1	8.8	101	5.9	182	14.6
	0.70		2.0		1.5		4.7		8.8		5.9		14.6
	1.41		2.0		1.5		4.7		8.8		5.9		14.6
	2.11		2.0		1.5		4.7		8.8		5.9		14.6
	2.81		2.0		1.5		4.7		8.5		5.9		14.6
	3.52		2.0		1.5		4.7		8.2		6.0		13.0
	4.22		1.9		1.5		4.4		5.3		5.9		11.5
	4.92		1.9		1.5		3.8		1.7		5.7		9.3
	5.62		1.8		1.3		2.1				3.8		
	6.33		1.0		1.2		*(7.14)		0.54		*(7.17)		1.4
	7.03		*(7.52)		*(7.17)								

*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright® 2015

Mazzei Injector Company, LLC
500 Rooster Drive, Bakersfield, CA 93307-9555 USA
www.mazzei.net

Injector Performance Table

Water Suction Capacity (METRIC)

REV 2014

Operating Pressure kg/cm ²		Model 1585X 40mm Threads		Model 1587 40mm Threads		Model 2081 50mm Threads		Model 2083X 50mm Threads		Model 3090 80mm Threads		Model 4091 100mm Threads	
Injector Inlet	Injector Outlet	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min
0.35	0.00	40.6	7.7	67.0	15.4	123	39.7	31.8	28.7	289	66.2	643	132
	0.07		4.7		6.4		39.7		9.9		56.7		94.6
	0.14		1.6		5.7		39.7				47.8		75.7
	0.21				3.4		13.5				28.7		53.0
	0.28		*(0.25)		*(0.29)		8.5		*(0.10)		*(0.28)		*(0.32)
0.70	0.00	57.4	15.2	94.7	17.0	174	39.7	49.6	35.3	409	91.2	810	177
	0.14		9.8		15.7		39.7		9.7		91.3		177
	0.35		2.7		6.5		29.5				55.0		117
	0.49				3.6		9.4				24.9		49.2
	0.56		*(0.46)		*(0.61)		1.9		*(0.17)		*(0.60)		*(0.62)
1.05	0.00	70.3	16.5	116	17.0	213	39.7	60.9	42.3	501	90.4	950	177
	0.35		9.9		11.6		39.3				90.0		177
	0.49		5.4		9.7		36.3				65.7		143
	0.70				6.2		13.4				34.9		45.4
	0.84		*(0.66)		*(0.95)		4.8		*(0.26)		*(0.95)		*(0.92)
1.41	0.00	81.2	19.4	134	16.8	245	39.7	71.5	47.7	578	89.3	1,030	177
	0.35		14.6		16.7		39.7		14.9		89.3		177
	0.70		7.5		11.0		29.5				73.8		170
	0.84		2.4		8.9		18.8				49.9		113
	1.05		*(0.89)		*(1.20)		9.5		*(0.40)		*(1.20)		*(1.23)
1.76	0.00	90.8	20.4	150	16.7	274	39.7	82.5	51.1	646	84.7	1,162	177
	0.35		17.3		16.7		39.7		27.0		84.5		177
	0.70		12.9		14.4		39.5				85.6		177
	1.05		3.1		9.8		25.4				58.6		124
	1.41		*(1.08)		*(1.55)		8.4		*(0.50)		*(1.51)		*(1.53)
2.11	0.00	99.4	20.3	164	16.6	301	39.7	87.4	53.5	708	82.5	1,257	177
	0.35		18.9		16.5		39.7		49.1		82.6		177
	0.70		15.8		16.9		39.7				82.5		177
	1.05		8.6		12.6		32.2				80.8		162
	1.41		*(1.36)		*(1.80)		21.5		*(0.62)		36.4		87.1
2.46	0.00	107	20.5	177	18.0	325	39.7	92.4	53.8	765	81.3	1,363	177
	0.35		20.0		17.9		39.7		42.2		81.3		177
	0.70		18.0		18.1		39.7		18.1		79.8		177
	1.05		12.8		15.8		39.5				80.0		177
	1.41		4.2		12.0		29.0				57.1		166
2.81	0.00	115	20.4	189	18.1	347	39.7	99.9	56.6	818	79.1	1,446	177
	0.35		20.2		17.9		39.7		58.0		79.1		177
	0.70		19.4		17.8		39.7		24.5		79.1		177
	1.05		16.2		17.5		39.7				79.2		177
	1.41		9.2		15.4		33.0				70.0		177
3.16	0.00	122	20.7	201	18.1	368	39.7	105	59.7	867	44.9	1,522	177
	0.35		20.4		16.3		39.7		47.2		79.4		177
	0.70		20.0		16.4		39.7		30.6		79.4		177
	1.05		18.1		16.2		39.7				79.0		177
	1.41		13.2		16.2		38.2				60.6		177
3.52	0.00	128	20.4	212	16.4	388	39.7	108	74.1	914	77.9	1,575	177
	0.35		20.1		16.3		39.7		80.6		77.9		177
	0.70		19.9		16.3		39.7		36.5		77.9		177
	1.05		18.7		16.3		39.7				78.0		177
	1.41		15.8		16.2		39.7				75.3		177

*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright® 2015

Mazzei Injector Company, LLC
500 Rooster Drive, Bakersfield, CA 93307-9555 USA

www.mazzei.net

Injector Performance Table

Water Suction Capacity (METRIC)

REV 2014

Operating Pressure kg/cm ²		Model 1585X 40mm Threads		Model 1587 40mm Threads		Model 2081 50mm Threads		Model 2083X 50mm Threads		Model 3090 80mm Threads		Model 4091 100mm Threads	
Injector Inlet	Injector Outlet	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min	Motive Flow l/min	Water Suction l/min
4.22	0.00	141		232	20.1	425	17.4	119	39.7	1,001	85.1	1,741	78.3
	0.35				20.1		17.4		39.7		85.9		78.3
	0.70				20.0		17.4		39.7		53.6		78.3
	1.05				19.3		17.4		39.7		32.8		78.3
	1.41				18.2		17.4		39.7				177
	2.11				11.0		17.1		37.8				177
	2.46				4.8		16.3		32.0				174
	2.81						13.4		24.0				159
	3.16		*(2.69)				7.4		*(3.52)				106
					*(3.51)						*(1.26)		*(3.44)
4.92	0.00	152		251	19.9	459	17.4	128	39.7	1,082	90.2	1,874	77.5
	0.35				19.9		17.4		39.7		95.2		77.5
	0.70				19.9		17.4		39.7		79.5		174
	1.05				19.6		17.4		39.7		45.3		174
	1.41				18.9		17.4		39.7		27.6		174
	2.11				16.4		17.3		39.7				174
	2.81				4.3		16.6		33.3				174
	3.16						13.1		27.7				174
	3.52						9.5		20.5				117
	3.87		*(3.14)				3.6		*(4.11)		8.9		*(4.25)
5.62	0.00	162		268	20.2	491	17.4	132	39.7	1,156	91.7	2,014	77.5
	0.35				20.2		17.4		39.7		95.8		170
	0.70				20.2		17.4		39.7		88.1		170
	1.05				20.2		17.4		39.7		52.0		170
	1.41				19.6		17.4		39.7		36.2		170
	2.11				18.1		17.4		39.7				170
	2.81				13.2		17.2		38.1				170
	3.52						14.5		31.9				170
	4.22						5.8		17.0				113
	4.57		*(3.59)				3.2		3.8				53.0
6.33	0.00	172		284	19.5	521	17.3	138	39.7	1,226	93.7	2,154	77.5
	0.35				19.5		17.3		39.7		96.3		159
	0.70				19.5		17.3		39.7		93.4		159
	1.41				19.1		17.3		39.7		68.4		159
	2.11				18.6		17.3		39.7		40.2		159
	2.81				17.0		17.3		39.7				159
	3.52				6.7		17.1		37.9				151
	4.22						13.1		28.9				147
	4.92						3.9		11.3				106
	5.27		*(4.04)				*(5.20)		*(5.31)				53.0
7.03	0.00	182		299	19.2	549	17.3	149	39.7	1,293	91.3	2,271	77.5
	0.35				19.2		17.3		39.7		96.1		159
	0.70				19.2		17.3		39.7		91.4		159
	1.41				18.9		17.3		39.7		63.6		159
	2.11				17.8		17.3		39.7		55.8		159
	2.81				17.2		17.3		39.7				159
	3.52				12.2		17.2		39.2				159
	4.22				0.92		16.7		37.4				159
	4.92						11.3		26.0				147
	5.62		*(4.44)				3.9		7.6				56.8
8.44	0.00			328		601	17.0	163	39.7		91.8		
	0.35						17.0		39.7				
	0.70						17.0		39.7				
	1.41						17.0		39.7				
	2.11						17.0		39.7				
	2.81						17.0		39.7				
	3.52						17.0		38.6				
	4.22						16.9		37.5				
	4.92						16.9		33.0				
	5.62						14.2		19.5				
	6.33						6.6		*(2.57)				
	7.03						*(6.88)		*(7.09)				

*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright® 2015

Mazzei Injector Company, LLC
500 Rooster Drive, Bakersfield, CA 93307-9555 USA
www.mazzei.net

Injector Performance Table

REV 2014

Air Suction Capacity (METRIC)												REV 2014													
Operating Pressure kg/cm ²		Model 287 15mm Threads		Model 384 15mm Threads		Model 484 15mm & 20mm Threads		Model 484X 20mm Threads		Model 584 15mm & 20mm Threads		Model 684 20mm Threads													
Injector INLET	Injector OUTLET	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min												
0.35	0.00	1.1	<0.25	2.5	0.28 <0.10 0.16 <0.10 <0.10	4.3	2.6 0.94 0.16 <0.10 <0.10	4.3	3.7 1.2 0.31 0.22 *(0.25)	7.6	4.1 1.5 0.60 0.34 *(0.31)	12.7	4.2 2.6 1.4 0.47 *(0.30)												
	0.07																								
	0.14																								
	0.21																								
	0.28																								
0.70	0.00	1.2	0.47 <0.25	3.6	1.6 0.73 0.16	6.1	4.5 1.4 0.34 0.16 <0.10	6.1	6.1 1.8 0.54 0.18 *(0.53)	10.7	6.8 2.7 0.81 0.36 *(0.63)	18.0	6.2 4.4 1.7 0.71 *(0.60)												
	0.14																								
	0.35																								
	0.49																								
	0.56																								
1.05	0.00	1.6	0.94 <0.25	4.4	3.1 0.51 0.28	7.5	5.9 1.0 0.61 0.28 0.12	7.5	8.3 1.3 0.72 *(0.61)	13.1	8.2 2.1 1.2 0.46 0.23	22.0	7.3 3.3 2.0 1.0 *(0.91)												
	0.35																								
	0.49																								
	0.70																								
	0.84																								
1.41	0.00	1.9	1.4 <0.25	5.1	4.1 1.0 0.30	8.6	6.9 2.2 0.60 0.39 0.21	8.6	10.1 2.5 0.69 0.47 *(0.93)	15.2	9.7 3.8 1.3 0.82 0.41	25.4	11.1 7.0 2.6 1.8 *(1.16)												
	0.35																								
	0.70																								
	0.84																								
	1.05																								
1.76	0.00	2.2	1.6 <0.25	5.7	4.5 1.4 0.54	9.7	7.4 2.8 0.97 0.33 0.16	9.7	11.7 3.9 0.98 0.60 *(1.16)	17.0	10.9 4.9 2.2 0.94 0.35	28.4	13.0 9.2 3.9 1.7 *(1.48)												
	0.35																								
	0.70																								
	1.05																								
	1.41																								
2.11	0.00	2.4	1.6 <0.25	6.2	4.7 1.7 0.70 0.36	10.6	7.8 4.2 1.8 0.79 0.32 0.14	10.6	12.9 4.9 1.5 0.88 *(1.20)	18.6	12.3 6.4 3.1 1.5 0.86 0.30	31.1	14.3 11.1 5.6 2.8 1.6 0.63												
	0.35																								
	0.70																								
	1.05																								
	1.41																								
2.46	0.00	2.6	1.8 <0.25	6.7	4.9 1.8 0.85 0.48 0.27	11.4	8.2 5.5 2.5 1.2 0.64 0.32	11.4	14.4 6.7 2.2 1.1 0.86 *(1.65)	20.1	13.4 8.7 4.4 2.4 1.3 0.81	33.6	15.6 12.2 7.7 4.1 2.6 *(2.07)												
	0.35																								
	0.70																								
	1.05																								
	1.41																								
2.81	0.00	2.8	2.1 0.47 <0.25	7.2	5.0 2.1 1.0 0.61 0.36	12.2	8.5 5.9 3.5 1.7 0.88 0.56 0.21	12.2	15.5 8.0 3.4 1.5 1.1 0.39 *(1.84)	21.4	14.5 9.2 5.1 3.2 1.9 1.2 0.72	36.0	16.5 12.8 9.9 5.5 3.8 2.3 1.6												
	0.35																								
	0.70																								
	1.05																								
	1.41																								
3.16	0.00	3.0	2.1 0.94 <0.25	7.6	5.4 2.5 1.3 0.78 0.49 0.33	13.0	9.0 6.4 3.9 2.1 1.3 0.81 0.44 0.21	13.0	15.5 9.4 4.2 1.9 1.2 0.98 *(1.78)	22.7	14.9 10.1 5.9 4.4 2.7 1.8 1.2 0.66	38.1	17.4 14.1 11.1 7.3 4.6 3.0 1.9 *(2.64)												
	0.35																								
	0.70																								
	1.05																								
	1.41																								
3.52	0.00	3.1	2.1 1.1 <0.25	8.0	5.9 2.9 1.6 0.93 0.60 0.43	13.7	9.8 7.2 4.2 2.4 1.6 1.3 0.67 0.41 0.20	13.7	16.0 11.1 5.5 2.5 1.5 1.1 *(2.04)	24.0	15.6 10.6 7.5 4.8 3.6 2.3 1.6 1.0 0.64	40.2	19.8 15.5 13.4 9.2 5.6 3.7 2.7 1.7 0.98												
	0.35																								
	0.70																								
	1.05																								
	1.41																								
<p>*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).</p>																									
<p>Copyright © 2015 Mazzei Injector Company, LLC 500 Rooster Drive, Bakersfield, CA 93307-9555 USA www.mazzei.net</p>																									



Injector Performance Table

Air Suction Capacity (METRIC)												REV 2014	
Operating Pressure kg/cm ²		Model 287 15mm Threads		Model 384 15mm Threads		Model 484 15mm & 20mm Threads		Model 484X 20mm Threads		Model 584 15mm & 20mm Threads		Model 684 20mm Threads	
Injector INLET	Injector OUTLET	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min
4.22	0.00	3.4	2.8	8.8	6.3	15.0	9.5	15.0	17.2	26.3	17.1	44.0	20.2
	0.35				3.7		8.0		14.3		12.6		16.5
	0.70				0.5		5.5		7.7		9.9		14.8
	1.05				1.3		3.6		4.8		6.4		13.0
	1.41				0.85		2.4		2.4		4.7		8.1
	2.11				0.45		1.1		1.3		2.6		4.4
	2.46				0.26		0.76				2.0		3.2
	2.81						0.59				1.3		2.4
	3.16		*(3.30)	*(3.33)		*(3.57)		*(2.43)	*(3.76)	*(3.52)	0.96	*(3.52)	1.5
4.92	0.00	3.7	3.3	9.5	6.8	16.2	9.7	16.2	18.7	28.4	17.2	47.6	20.2
	0.35				4.5		8.7		14.9		13.5		18.6
	0.70				2.6		6.8		9.8		11.1		16.6
	1.05				1.7		4.7		7.1		8.1		14.8
	1.41				1.1		3.3		3.5		6.0		12.7
	2.11				0.63		1.8		1.7		3.8		6.4
	2.81				0.41		1.0		1.1		2.2		3.8
	3.16						0.77				1.8		2.8
	3.52						0.48				1.2		2.1
	3.87		*(3.87)	*(3.68)		*(4.11)		*(2.86)	*(4.43)	*(4.10)	0.82	*(4.71)	1.3
5.62	0.00	4.0	3.3	10.1	7.5	17.3	10.1	17.3	19.0	30.3	17.9	50.9	20.2
	0.35				5.3		9.4		18.0		14.6		19.7
	0.70				3.1		7.5		13.6		12.3		17.3
	1.05				2.2		5.5		8.6		10.3		16.2
	1.41				1.5		4.0		4.7		7.5		15.1
	2.11				0.88		2.3		2.3		4.9		8.0
	2.81				0.58		1.4		1.4		3.3		5.1
	3.52				0.40		0.78		1.0		2.1		3.1
	4.22		*(4.43)	*(4.35)		*(4.64)		*(3.65)	*(5.10)	*(4.71)	0.83	*(4.71)	1.4
	4.57												
6.33	0.00	4.2	3.3	10.7	8.1	18.4	10.3	18.4	20.1	32.2	18.2	53.9	20.3
	0.35				6.0		9.6		18.7		15.4		19.9
	0.70				3.6		8.3		15.5		13.6		18.6
	1.41				1.9		4.8		7.5		9.3		16.2
	2.11				1.0		2.9		3.4		6.1		11.6
	2.81				0.73		2.0		2.1		4.1		6.9
	3.52				0.51		1.2		1.3		2.7		4.7
	4.22				0.38		0.75				1.8		3.3
	4.92		*(4.99)	*(4.99)		*(5.20)		*(3.81)	*(5.66)	*(5.34)	0.84	*(5.98)	1.4
	5.27												
7.03	0.00	4.4	3.3	11.3	8.4	19.3	10.3	19.3	20.9	33.9	18.5	56.9	20.5
	0.35				6.5		9.8		20.1		16.6		20.3
	0.70				4.2		8.9		17.2		14.3		19.8
	1.41				2.2		5.7		8.8		10.9		18.0
	2.11				1.2		3.6		4.8		6.8		15.5
	2.81				0.91		2.5		2.8		5.1		8.5
	3.52				0.67		1.6		1.8		3.6		6.1
	4.22				0.51		1.0				2.4		4.4
	4.92		*(5.55)	*(5.52)		*(5.83)		*(4.19)	*(6.33)	*(5.98)	0.96	*(5.98)	1.8
	5.62												
8.44	0.00	4.8	3.3	12.4	9.2	21.2	10.7	21.2	23.0	37.1	19.0	62.3	20.7
	0.35				7.2		10.3		22.2		18.1		20.4
	0.70				5.2		9.9		20.1		15.8		20.0
	1.41				2.9		7.2		12.3		13.0		18.8
	2.11				1.8		5.0		7.0		8.7		18.1
	2.81				1.2		3.6		3.9		6.5		12.8
	3.52				0.95		2.7		2.6		5.1		8.5
	4.22				0.72		1.9		1.9		3.6		6.4
	4.92				0.58		1.3		1.4		2.9		5.1
	5.62				0.47		0.95				2.0		3.9
	6.33		*(6.68)	*(6.81)		*(7.01)		*(5.00)	*(7.52)	*(7.17)	1.4	*(7.17)	1.7
	7.03										0.87		

*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright® 2015

Mazzei Injector Company, LLC
500 Rooster Drive, Bakersfield, CA 93307-9555 USA
www.mazzei.net

Injector Performance Table

REV 2014

Air Suction Capacity (METRIC)											
Operating Pressure		Model 784		Model 878-03		Model 885X-03		Model 978-03		Model 1078-03	
kg/cm ²		20mm Threads		25mm Threads		25mm Threads		25mm Threads		25mm Threads	
Injector INLET	Injector OUTLET	Motive Flow l/min	Air Suction l/min								
0.35	0.00		5.5		7.0		8.6		8.7		11.4
	0.07		4.6		2.5		4.2		2.4		3.0
	0.14		2.2		0.73		0.69		0.86		1.2
	0.21		1.0		0.19				0.42		0.70
	0.28	*(0.32)	0.46	(0.28)		(0.28)		(0.27)		(0.28)	*(0.31)
0.70	0.00		9.1		16.0		12.7		14.1		18.9
	0.14		7.4		4.0		7.1		5.2		7.6
	0.35		2.7		1.3		0.87		1.4		1.9
	0.49		0.94		0.42				0.60		0.73
	0.56	(0.63)	0.44	(0.61)	0.29	(0.53)		(0.63)		(0.57)	*(0.61)
1.05	0.00		13.6		17.0		18.1		17.9		22.9
	0.35		7.8		3.5		3.7		4.1		6.1
	0.49		4.1		1.8		1.6		2.6		3.7
	0.70		1.9		0.35				1.1		1.5
	0.84	(0.91)	0.90	(0.88)		(0.77)		(0.94)		(0.92)	*(0.91)
1.41	0.00		15.9		20.9		22.2		20.8		25.9
	0.35		10.0		5.9		6.4		6.8		10.4
	0.70		3.8		2.0		1.7		2.8		4.0
	0.84		2.3		1.2				1.9		2.6
	1.05	(1.23)	1.1	(1.16)	0.82	(0.98)		(1.18)		(1.22)	*(1.26)
1.76	0.00		18.9		21.1		26.9		22.6		28.7
	0.35		13.7		8.2		13.1		8.8		15.7
	0.70		6.6		3.2		3.3		4.1		6.7
	1.05		1.5		1.6		1.3		2.1		3.5
	1.41	(1.57)		(1.48)	0.58	(1.20)		(1.46)	0.81	(1.54)	1.6
2.11	0.00		22.7		24.0		31.5		23.5		33.3
	0.35		15.3		12.3		21.8		12.5		21.9
	0.70		9.6		5.3		5.8		5.9		9.6
	1.05		4.5		3.0		2.6		3.4		5.3
	1.41		2.0		1.4		0.98		1.8		2.8
2.46	0.00		21.9		24.5		41.2		22.7		34.9
	0.35		17.9		16.2		12.9		13.7		24.9
	0.70		14.0		6.6		33.9		40.7		52.6
	1.05		7.1		4.0		7.5		7.6		11.6
	1.41		3.8		2.2		3.7		5.2		6.4
2.81	0.00		25.0		26.3		38.1		24.5		37.7
	0.35		21.1		19.1		18.5		18.2		27.3
	0.70		16.9		8.3		10.0		9.5		14.8
	1.05		9.6		5.5		5.3		6.2		8.9
	1.41		5.4		3.1		3.2		4.0		6.1
3.16	0.00		3.3		2.2		2.1		2.6		3.8
	0.35		1.4		1.1		(1.90)		1.5		2.0
	0.70		(2.39)	(2.42)		(1.90)		(2.41)		(2.42)	*(2.35)
	1.05										4.5
	1.41										
3.52	0.00		26.6		31.5		36.4		25.8		40.5
	0.35		22.7		19.9		22.9		20.0		29.6
	0.70		18.2		9.8		12.8		11.0		18.1
	1.05		13.7		6.0		6.9		7.6		10.9
	1.41		7.0		4.2		4.3		5.2		7.4
3.16	0.00		4.4		2.4		3.0		3.4		5.3
	0.35		2.8		1.9		1.6		2.2		3.3
	0.70		1.2		1.0		(2.18)		1.3		(2.72)
	1.05		(2.67)	(2.70)		(2.18)		(2.72)		2.1	*(2.64)
	1.41										4.3
3.52	0.00		27.4		30.6		39.5		28.8		41.4
	0.35		24.5		23.0		23.4		22.8		31.3
	0.70		20.3		11.2		15.2		12.7		19.9
	1.05		16.8		7.6		8.3		9.1		12.1
	1.41		9.6		4.9		5.3		6.4		7.6
2.81	0.00		6.4		3.9		3.5		4.7		6.0
	0.35		4.3		2.1		2.3		3.2		4.1
	0.70		2.8		2.0		(2.53)		2.1		2.5
	1.05		(3.01)	1.3	(2.97)	0.53	(2.96)	1.1	(3.09)	1.4	(2.95)
	1.41										3.1

*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright® 2015

Mazzei Injector Company, LLC
500 Rooster Drive, Bakersfield, CA 93307-9555 USA

www.mazzei.net

Injector Performance Table

Air Suction Capacity (METRIC)

REV 2014

Operating Pressure kg/cm ²		Model 784 20mm Threads		Model 878-03 25mm Threads		Model 885X-03 25mm Threads		Model 978-03 25mm Threads		Model 1078-03 25mm Threads		Model 1583 40mm Threads	
Injector INLET	Injector OUTLET	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min
4.22	0.00	56.6	28.0	45.9	33.6	44.4	56.8	53.3	34.5	68.8	43.1	135	101
	0.35		27.1		25.9		27.5		26.9		36.0		70.9
	0.70		23.3		15.8		21.3		17.6		27.1		35.6
	1.05		20.8		9.5		10.8		11.6		16.3		24.8
	1.41		16.5		6.9		7.7		8.5		11.5		18.6
	2.11		7.3		3.6		4.1		5.0		6.6		9.8
	2.46		4.9		2.7		3.1		3.7		4.8		7.9
	2.81		3.8		2.0		1.4		2.6		3.4		5.6
	3.16		*(3.52)		2.3		*(3.02)		*(3.62)		1.7		*(3.47)
	0.00		*(3.60)		1.1						*(3.59)		4.9
4.92	0.00	61.1	28.3	49.6	36.3	48.0	63.9	57.5	34.7	74.3	47.4	146	113
	0.35		28.2		28.3		29.9		29.6		38.5		89.2
	0.70		25.8		19.2		21.8		23.2		31.8		47.3
	1.05		23.4		12.0		14.1		15.1		21.8		31.7
	1.41		21.8		9.0		10.6		10.8		15.0		22.5
	2.11		10.5		5.3		6.0		7.0		9.2		12.9
	2.81		6.3		3.2		3.6		4.3		5.8		8.5
	3.16		4.6		2.3		2.5		3.2		4.1		5.9
	3.52		3.5		1.9				2.2		3.3		5.6
	3.87		*(4.10)		1.0		*(3.59)		*(4.22)		1.3		*(3.99)
5.62	0.00	65.3	28.7	53.0	38.3	51.3	72.9	61.5	36.0	79.5	49.8	156	117
	0.35		28.3		30.6		28.8		31.8		42.2		93.5
	0.70		27.3		23.5		26.0		26.3		35.3		51.1
	1.05		25.5		14.6		16.1		17.9		27.2		34.2
	1.41		24.3		10.9		13.5		13.1		18.6		27.7
	2.11		16.1		6.6		7.6		8.9		11.6		17.7
	2.81		8.6		4.2		4.7		5.4		8.0		11.2
	3.52		5.5		2.7		2.9		3.5		4.8		7.1
	4.22		2.9		1.8				1.9		2.9		5.8
	4.57		1.6		1.1		*(4.01)		1.7		2.1		*(4.92)
6.33	0.00	69.3	29.2	56.2	40.2	54.4	79.3	65.2	41.4	84.3	53.2	165	123
	0.35		29.2		32.8		32.2		32.9		45.4		98.3
	0.70		29.1		26.6		29.1		28.8		38.5		65.8
	1.41		26.5		12.7		16.5		15.6		23.0		33.6
	2.11		22.7		8.1		9.3		10.6		13.8		22.3
	2.81		11.9		5.7		6.1		7.5		9.8		14.8
	3.52		7.7		3.7		4.1		4.6		7.0		10.3
	4.22		5.2		2.4		2.1		3.4		4.3		6.0
	4.92		2.7		1.6				2.0		2.7		3.3
	5.27		1.7		1.0		*(4.64)		1.7		2.0		*(5.14)
7.03	0.00	73.0	29.2	59.3	41.85	57.3	87.3	68.8	42.9	88.8	55.0	174	131
	0.35		29.6		34.1		34.6		35.9		48.6		109
	0.70		29.0		29.6		30.7		31.8		41.4		78.5
	1.41		27.5		14.6		20.1		18.4		29.6		38.1
	2.11		24.8		9.5		11.3		13.0		17.5		26.0
	2.81		16.8		6.8		7.5		9.0		12.1		18.1
	3.52		9.8		4.7		5.3		6.2		8.5		12.5
	4.22		6.8		3.4		3.6		4.6		5.9		9.0
	4.92		4.5		2.4				3.2		3.9		8.2
	5.62		2.3		1.3		*(5.13)		2.1		2.6		*(5.72)
8.44	0.00	80.0	29.9	64.9	46.3	62.8	98.8	75.3	44.3	97.3	58.8	191	139
	0.35		30.0		38.2		37.6		38.6		52.3		117
	0.70		29.8		33.4		34.5		33.8		46.2		102
	1.41		29.5		19.7		24.9		22.8		36.7		50.5
	2.11		27.0		12.3		13.4		15.7		22.1		33.5
	2.81		26.0		9.0		10.1		11.3		15.8		25.1
	3.52		16.2		6.8		7.9		7.5		11.8		18.7
	4.22		10.6		5.1		5.4		6.3		9.0		13.8
	4.92		7.8		3.7		4.6		4.7		6.6		9.7
	5.62		5.5		2.7		1.8		3.6		4.8		9.3
	6.33		3.4		2.1				2.6		3.1		7.6
	7.03		*(7.17)		1.1		*(5.98)		*(7.24)		1.8		*(6.92)

*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright® 2015

Mazzei Injector Company, LLC

500 Rooster Drive, Bakersfield, CA 93307-9555 USA

www.mazzei.net

Injector Performance Table

Air Suction Capacity (METRIC)												REV 2015.12.02	
Operating Pressure kg/cm ²		Model 1584 40mm Threads		Model 1585X 40mm Threads		Model 1587 40mm Threads		Model 2081 50mm Threads		Model 3090 80mm Threads		Model 4091 100mm Threads	
Injector INLET	Injector OUTLET	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min
0.35	0.00	68.3	22.1	38.9	26.6	64.2	31.1	166	199	392	338	553	441
	0.07		18.8		5.6		10.3		28.8		299		192
	0.14		15.0		3.2		7.4		10.2		29		73.6
	0.21		9.7				4.1		4.6		23		28.3
	0.28		*(0.29)		*(0.25)		*(0.29)		2.3		16		767
0.70	0.00	96.6	46.2	55.0	30.6	90.8	60.3	166	392	715	305	715	299
	0.14		34.1		9.4		28.8		29		178		76.4
	0.35		17.5		5.5		4.6		23		138		31.1
	0.49		9.7				2.3		16		14.1		767
	0.56		*(0.60)		*(0.46)		*(0.61)		16		14.1		767
1.05	0.00	118	67.9	67.4	55.3	111	72.5	204	247	480	464	871	1,149
	0.35		33.8		8.8		20.1		71		316		198
	0.49		21.5		5.5		12.6		38		199		110
	0.70		11.2				6.4		30		123		50.9
	0.84		*(0.91)		4.4		4.2		19		56.6		56.6
1.41	0.00	137	80.2	77.8	61.7	128	81.6	235	286	554	537	1,011	1,308
	0.35		48.2		14.6		30.3		115		401		351
	0.70		19.3		6.0		12.0		42		184		124
	0.84		14.7		3.0		8.8		37		139		79.2
	1.05		*(1.20)		5.9		*(1.20)		29		*(1.20)		42.4
1.76	0.00	153	87.3	87.0	68.6	143	92.3	263	316	619	585	1,120	1,534
	0.35		60.8		22.9		42.9		172		472		498
	0.70		31.0		9.5		20.5		65		255		203
	1.05		15.6		3.8		9.0		41		148		96.2
	1.41		*(1.51)		5.6		4.6		25		*(1.51)		39.6
2.11	0.00	167	91.5	95.3	79.8	157	108	288	346	678	649	1,226	1,778
	0.35		72.1		28.7		54.0		221		537		920
	0.70		46.9		12.1		25.8		100		320		297
	1.05		25.6		6.9		14.1		50		182		150
	1.41		13.4				8.2		42		119		82.1
	1.76		*(1.83)		4.7		*(1.80)		20		*(1.79)		82.1
2.46	0.00	181	97.2	103	82.8	170	108	311	377	733	683	1,329	1,747
	0.35		81.8		36.9		67.7		264		587		1,098
	0.70		58.2		16.1		33.4		135		352		362
	1.05		34.1		9.7		19.6		66		212		223
	1.41		18.7		4.9		12.7		51		141		127
	1.76		*(2.14)		10.6		8.8		42		92.8		67.9
2.81	0.00	193	100	110	83.5	181	120	333	403	783	641	1,416	1,905
	0.35		89.0		41.2		89.5		299		586		1,257
	0.70		69.7		21.3		40.9		162		374		453
	1.05		46.6		11.7		24.7		94		251		294
	1.41		28.1		7.8		17.0		59		166		189
	1.76		18.1		1.2		12.6		51		116		116
	2.11		*(2.46)		10.3		*(2.33)		40		*(2.28)		62.2
3.16	0.00	205	104	117	108	193	126	353	424	831	702	1,503	2,030
	0.35		93.2		49.7		98.1		329		661		1,353
	0.70		74.4		24.1		43.0		204		480		557
	1.05		52.4		15.3		27.7		122		354		348
	1.41		34.8		10.1		18.8		68		224		246
	1.76		23.4		5.7		13.3		58		162		161
	2.11		15.3				8.9		51		110		99.1
	2.46		10.0		*(2.02)		7.1		38		*(2.53)		14.1
3.52	0.00	216	106	123	96.1	203	127	372	450	876	730	1,586	2,120
	0.35		98.1		61.1		104		359		668		1,458
	0.70		82.8		26.7		52.6		245		551		764
	1.05		62.8		17.9		33.3		152		371		402
	1.41		45.6		12.9		24.4		92		258		305
	1.76		32.2		8.2		17.6		66		201		212
	2.11		22.2		3.0		10.7		59		144		141
	2.46		15.0				9.2		52		106		87.7
	2.81		*(2.99)		8.7		*(2.88)		35		*(2.85)		87.7

*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright® 2015

Mazzei Injector Company, LLC
500 Rooster Drive, Bakersfield, CA 93307-9555 USA

www.mazzei.net

Injector Performance Table

Air Suction Capacity (METRIC)												REV 2015.12.02	
Operating Pressure kg/cm ²		Model 1584 40mm Threads		Model 1585X 40mm Threads		Model 1587 40mm Threads		Model 2081 50mm Threads		Model 3090 80mm Threads		Model 4091 100mm Threads	
Injector INLET	Injector OUTLET	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min	Motive Flow l/min	Air Suction l/min
4.22	0.00	236	112	135	109	222	144	407	494	959	807	1,730	2,248
	0.35		103		85.9		118		408		736		1,642
	0.70		90.1		36.7		76.4		315		610		1,489
	1.05		74.4		24.3		45.3		199		439		546
	1.41		56.9		16.8		33.8		142		297		393
	2.11		32.2		8.7		19.0		72		196		249
	2.46		25.0		4.7		15.0		66		147		178
	2.81		17.5				11.0		60		105		121
	3.16		*(3.62)		12.2		*(3.51)		49		*(3.44)		79.2
	0.00		115		123				533		854		2,282
4.92	0.35	255	109	146	100			440		1,036	451	1,870	1,798
	0.70		98.1		42.6						716		1,602
	1.05		84.5		28.3						594		756
	1.41		71.1		21.9						191		506
	2.11		43.4		12.6						93		334
	2.81		26.6		5.8						72		198
	3.16		20.3								67		144
	3.52		15.6								59		96.2
	3.87		*(4.22)		10.0		*(3.14)		*(4.11)		45		76.4
	0.00		117		130						567		2,302
5.62	0.35	273	113	156	110			471		1,108	487	2,006	1,891
	0.70		105		56.7						422		1,868
	1.05		94.2		37.4						329		1,359
	1.41		82.2		27.8						229		597
	2.11		55.3		16.2						132		387
	2.81		37.6		10.4						83		269
	3.52		23.1		0.69						72		152
	4.22		13.1								57		84.9
	4.57		*(4.78)		8.4		*(3.59)		*(4.68)		40		67.9
	0.00		118		137						934		
6.33	0.35	290	116	165	110			1,175		1,175	991		
	0.70		110		65.2						962		
	1.41		91.4		31.0						906		
	2.11		67.1		19.7						625		
	2.81		46.2		13.0						376		
	3.52		32.2		6.2						296		
	4.22		21.8								216		
	4.92		12.5								140		
	5.27		*(5.41)		8.4		*(4.04)				70.8		
	0.00		118		150						22.6		
7.03	0.35	305	119	174	118			1,238		1,238	934		
	0.70		115		89.0						877		
	1.41		98.4		36.2						628		
	2.11		79.4		24.3						573		
	2.81		57.5		15.8						357		
	3.52		42.1		10.3						280		
	4.22		29.1		3.3						203		
	4.92		20.0								148		
	5.62		11.8								104		
	0.00		122		159						42.4		
8.44	0.35	334	121	191	123						934		
	0.70		120		110						877		
	1.41		112		47.3						628		
	2.11		98.4		30.6						573		
	2.81		80.1		21.8						357		
	3.52		61.5		16.7						280		
	4.22		46.6		10.4						203		
	4.92		35.7		3.9						148		
	5.62		25.9								104		
	6.33		17.5								42.4		
	7.03		*(7.24)		10.3		*(5.29)						
	0.00		122		159								

*Numbers in parenthesis indicate the injector outlet pressure when suction stops (Zero Suction Point).

Copyright® 2015

Mazzei Injector Company, LLC
500 Rooster Drive, Bakersfield, CA 93307-9555 USA
www.mazzei.net